



CARTRIDGE ACTUATED DEVICES, INC
51 DWIGHT PLACE FAIRFIELD, NJ 07004

REVISION: A DATE: 022609

HAZARDOUS CHEMICAL MATERIAL SAFETY DATA SHEET
(Conforms to the requirements of 29 CFR 1910.1200)

I. PRODUCT IDENTITY: **Cartridges, Power device, 1.4s UN 0323EX-9311346
(Squib 073091-1)**

CARTRIDGE ACTUATED DEVICES, INC.
51 Dwight Place
Fairfield, N.J. 07004

24 HOUR EMERGENCY PHONE #
IN U.S.A.: 800-424-9300
OUTSIDE U.S.A.:
202-483-7616 CALL COLLECT
FIRE, SPILL, EMERGENCY ONLY

Prepared by CAD Engineering
Telephone Number: 973-575-1312

Material(s) described is/are: Company Proprietary Explosive
Device and by-products of
initiation.

II. HAZARDOUS INGREDIENTS AND EXPOSURE LIMITS: N/A

Chemical and common name of Hazardous chemical ingredients:

** COMMON NAME	CAS NO.
Nitroglycerin	55-63-0
Nitrocellulose	90004-70-0
Lead Styphnate	15245-44-0

III. PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point	N/A	Solubility in water	slightly
Specific gravity	N/A	Ph	N/A
Vapor Pressure	N/A	Evaporation Rate	N/A
% Volatile	NIL		

IV. FIRE, EXPLOSION AND REACTIVITY HAZARD DATA

DANGER Extremely Flammable --EXPLOSIVE--
Keep away from heat and keep shunted.

Flash point:	N/A
Flammable Limits:	None, Explosive Device
Auto-ignition temperature:	325° F
Extinguishing media:	Dry, Chemical Extinguisher, water *(see next note)
Special Fire-Fighting procedures:	Don't fight fires directly involving explosives
Grounding Procedure:	Keep shunted when handling or during storage



CARTRIDGE ACTUATED DEVICES, INC
51 DWIGHT PLACE FAIRFIELD, NJ 07004

REVISION: A DATE: 022609

Stability Considerations: Stable
Incompatibility: None if cartridge remains intact

** All information applicable only if the cartridge ruptures before initiation.

Hazardous decomposition products: None
Hazardous products of combustion: Flame, high heat in small quantities, carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen cyanide, hydrochloric acid and trace amounts of lead.
Hazardous Polymerization: None

V. HEALTH HAZARD DATA:

Emergency and First Aid Procedure:
Treat burns and any laceration by cleaning and applying sterile bandages. Transport individual for further medical treatment.

Primary Route of Entry: N/A (cartridge is intact)
Cancer Information: None
Reported effects on Humans: N/A
Other: N/A (cartridge is intact)

VI. SPILL AND LEAK PROCEDURES

Steps to be taken if material is spilled:

Clean spill after liberally wetting down with solvent (Acetone, Butyl Acetate, Alcohol or water) by wiping material up with paper towels or with cotton rag. Keep a fire extinguisher present.

Waste Disposal Method:

Remotely initiate individual actuators in a restraining fixture or burn in the open in an isolated location. Remotely ignite with slow burning train or electrically initiated squib. Disposal must be in accordance with local, state, and Federal regulations.
Call Cartridge Actuated Devices for assistance, if needed.



CARTRIDGE ACTUATED DEVICES, INC
51 DWIGHT PLACE FAIRFIELD, NJ 07004

REVISION: A DATE: 022609

VII. APPLICABLE CONTROL MEASURES:

Appropriate Hygienic Practices:	N/A
Personal Protective Equipment:	Safety glasses grounding devices (ground straps and/or conductive footwear).
Work Practices:	Avoid high temperatures. Wear personal protective equipment. Work behind shielding and keep the actuator shunted.
Handling and Storage precaution:	Recommended storage, 70° F.
Engineering Controls:	Work with device in a shielded area.
Protective Measures during Repair and Maintenance:	Eliminate static discharge sources. Avoid flame or high heat. Shield device when working with it.

DISCLAIMER: The above information taken from various published and unpublished sources is believed to be accurate and represent the best information currently available to us. However, we make no warranty of the accuracy of such information express or implied, and assume no liability resulting from its use. Users should make their own investigation to determine suitability of the information for their particular purposes.

THIS UNIT IS NOT USER SERVICEABLE. DO NOT ATTEMPT DOWNLOADING OR DISASSEMBLING.

Net Reactive Material Content not to exceed 0.115 grams